


CONVECTION OVENS



Single oven
Gaggenau 200 Series
Width 27" (70 cm)

Right-hinged
EB 290-600
anthracite

EB 290-630
aluminum

Left-hinged
EB 291-600
anthracite

EB 291-630
aluminum

220 – 240 V / 60 Hz

EB 290/291-600/630

Oven interior volume: 3.02 cb. ft.
 Interior dimensions:
 W 21½" x H 14⅜" x D 15¾"

Electronic precision temperature control from 120° F – 570° F, from 120° F – 170° F in 5° F increments and from 170° F – 570° F in 10° F increments.

100 W halogen lighting.
 Super Quick preheating.
 Large function display.
 Automatic cooking time.
 Actual temperature display:
 "Thermo Test"
 Meat probe programmable with digital read out from 85° F to 210° F and automatic shut-off.
 Universal heating system with ten cooking modes.
 Economy program.
 Proofing.
 Baking stone socket.
 Rotisserie rotary spit.
 Smart pyrolytic self-cleaning.
 Porcelain interior.
 Catalyst for air cleaning.
 Cooled housing.
 Heat-insulated door with four-fold glazing.
 Child and vacation lock.
 Glass door opening through 180°.

Included accessories:

One wire rack, one baking tray, one broil pan, meat probe, rotary spit.

Optional accessories:

- PS 027-001** Baking stone with pizza peel, without heating element.
- BS 020-002** Set of two pizza peels.
- BT 026-001** Cast roaster, without heating element, needs GR 027-001.
- GR 027-001** Special wire rack for EB 290, needed for BT 026-001.
- HZ 026-001** Heating element needed for baking stone and cast roaster.
- KB 091-054** Baking tray.
- GP 091-054** Roasting/broil pan.
- GR 095-054** Wire rack with opening for broil pan.
- GR 090-054** Wire rack without opening, extra strong.
- BK 200-002** Special shorter control knobs (2).

Planning notes:

4' Power cable (hardwire required).
 Hinging must be specified when ordering as the door is not interchangeable.

When planning a corner solution, pay attention to the 90° door opening angle.

Plan a minimum distance of 2" between two ovens installed side by side when handles in the middle—or ¾" when centered around hinged sides.

Depth of handle: 3⅜".

Total rating: 4.2 kW
 Total Amps: 20

