

**HÄFELE**

at

**cabinet :: accessories**  
UNLIMITED

- UL® and CSA® Listed  
Tested safe power source for use with Häfele lights.
- Electronic short circuit protection feature.  
When short is detected, automatically turns off.  
Upon correction of problem transformer automatically restarts.
- 100% factory tested
- Modular plugs -  
No electrician or hard wiring required.
- Radio frequency interference protection.
- Emits no audible noise- Sound rating A+
- Energy efficient -  
If lights are turned off, transformer senses no signal and automatically turns off.
- Moisture and shock resistant.
- Soft start circuitry maximizes lamp life.
- Mounting instructions included.



**8** Interior Accessories  
Wardrobe Accessories  
Storage Systems  
Furniture Lighting

Dimensional data not binding.  
We reserve the right to alter specifications without notice.

**8.48** TCH 02

## Transformers

### Electronic Transformer

Primary: 120V  
Secondary: Max 60 watt - Min 20 watts-11.5V  
45mm wide x 70mm high x 24mm deep.

Secondary cord with AMP socket, transformer plugs into wall outlet - **requires** mounting block 823.24.418 for hook-up of more than one light.  
Finish: plastic



Wattage	Secondary cord length	Electrical Plugs	Color	Cat. No.
20 watts	10 feet	2 prong	black	823.24.450
20 watts	1 foot	2 prong	black	823.24.455
60 watts	10 feet	3 prong	black	823.24.460
60 watts	10 feet	3 prong	white	823.24.480

Packing: 1 pc.

### Electronic Transformer

Primary: 120 Volt, 2-pronged electrical plug  
Secondary: Max 60 watt - Min 20 watts - 11.5V  
68mm long x 38mm wide x 30mm high.

13' primary cord with AMP socket and 4" secondary cord and adhesive tape for fitting to shelves - requires mounting block 823.24.418 for hook-up of more than one light.



Cat. No. 823.24.436

Packing: 1 pc.

### Mounting Block

for connection of up to six lights not exceeding 60 watts  
Finish: plastic, black



Cat. No. 823.24.418

Packing: 1 pc.

